



Main

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	IMX+OF
Signal contacts composition	1 C/O
[Ie] rated operational current	DC-12 : 2 A DC 48 V AC-12 : 2 A AC 50 Hz 48 V
Control circuit voltage	48 V DC 48 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 2.4 mm ² flexible with cable end Clamp terminal 1 cable(s) 3 mm ² flexible Clamp terminal 2 cable(s) 2.4 mm ² rigid Clamp terminal 1 cable(s) 5 mm ² rigid
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.