



Main

| | |
|--------------------------------|--|
| Range | Acti 9 Clario Librio Prodis |
| Product or component type | Double OC or fault contact |
| Device short name | OF and OF or OF and SD |
| Signal contacts composition | 2 C/O |
| [le] rated operational current | 6 A AC 50/60 Hz 240 V 3 A AC 50/60 Hz 415 V 6 A DC 24 V 2 A DC 48 V 1 A DC 130 V |
| 9 mm pitches | 1 |

Complementary

| | |
|-------------------------|--|
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| Height | 84 mm |
| Width | 9 mm |
| Depth | 73 mm |
| Colour | White |
| Connections - terminals | Clamp terminal 2 rigid cable(s) 1.5 mm ² max Clamp terminal 2 flexible cable(s) 1.5 mm ² max Clamp terminal 1 rigid cable(s) 2.5 mm ² max Clamp terminal 1 flexible cable(s) 2.5 mm ² max |
| Wire stripping length | 9 mm |
| Tightening torque | 1 N.m |
| Product compatibility | C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40 |

Environment

| | |
|---------------------------------------|-------------------------------------|
| Standards | EN/IEC 60947-5-1 |
| IP degree of protection | IP20 conforming to EN/IEC 60947-5-1 |
| Pollution degree | 3 conforming to EN/IEC 60947-5-1 |
| Tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 1001 - Schneider Electric declaration of conformity |