



### Main

Range	Acti 9 Clario Librio Prodis
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
Control circuit voltage	12...24 V DC 12...24 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40

### Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1216 - <a href="#">Schneider Electric declaration of conformity</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.