

EZC100B3015

circuit breaker Easypact EZC100B - TMD - 15
A - 3 poles 3d



Main

Device short name	Easypact EZC100B
Circuit breaker application	Distribution
Poles description	3P
Protected poles description	3t
Network type	AC DC
Network frequency	50/60 Hz
[In] rated current	100 A (40 °C)
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
[Ue] rated operational voltage	550 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker rating code	B
Breaking capacity	Icu 7.5 kA at 400...415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 10 kA at 110...130 V AC 50/60 Hz conforming to IEC 60947-2 Icu 7.5 kA at 380 V AC 50/60 Hz conforming to IEC 60947-2 Icu 10 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 5 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu 2.5 kA at 550 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 0.625 kA 550 V AC 50/60 Hz conforming to IEC 60947-2 Ics 1.25 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 1.875 kA 380 V AC 50/60 Hz conforming to IEC 60947-2 Ics 1.875 kA 400/415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 2.5 kA 110/130 V AC 50/60 Hz conforming to IEC 60947-2 Ics 2.5 kA 220/230/240 V AC 50/60 Hz conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A
Trip unit technology	Thermal-magnetic
Trip unit rating	15 A (50 °C)
Protection type	Overload protection Short-circuit protection
Pollution degree	3 conforming to IEC 947-1 3 conforming to IEC 60664-1

Complementary

Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front

Mechanical durability	8500 cycles
Electrical durability	Category A: 1500 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2
Connection pitch	25 mm
Local signalling	Positive contact indication
Neutral protection setting	Without protection
Earth-leakage protection	Without
Height	130 mm
Width	75 mm
Depth	60 mm

Environment

Standards	GB 14048.2 IEC 60947-2 JIS C8201-2-2 NEMA AB1
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C
RoHS EUR conformity date	0734
RoHS EUR status	Compliant