



### Main

Device short name	Easypact EZC100F
Circuit breaker application	Distribution
Poles description	3P
Protected poles description	3t
Network type	AC DC
Network frequency	50/60 Hz
[In] rated current	100 A ( 40 °C )
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
[Ue] rated operational voltage	250 V DC conforming to IEC 60947-2 550 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker rating code	F
Breaking capacity	Icu 5 kA at 125 V DC 1P conforming to IEC 60947-2 Icu 5 kA at 250 V DC 2P conforming to IEC 60947-2 Icu 25 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 10 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 7.5 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu 5 kA at 550 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 2.5 kA 550 V AC 50/60 Hz conforming to IEC 60947-2 Ics 2.5 kA 125 V DC conforming to IEC 60947-2 Ics 2.5 kA 250 V DC conforming to IEC 60947-2 Ics 3.75 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 5 kA 380...415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 12.5 kA 220...240 V AC 50/60 Hz conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A
Trip unit technology	Thermal-magnetic
Trip unit rating	16 A ( 50 °C )
Protection type	Overload protection Short-circuit protection
Pollution degree	3 conforming to IEC 60947

### Complementary

Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Mechanical durability	8500 cycles
Electrical durability	Category A: 1500 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2
Connection pitch	25 mm

Local signalling	Positive contact indication
Neutral protection setting	Without protection
Earth-leakage protection	Without
Height	130 mm
Width	75 mm
Depth	60 mm

## Environment

IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C
RoHS EUR conformity date	0843
RoHS EUR status	Compliant