

EZCV250N3150

circuit breaker Easypact EZCV250N - TMD -
150 A - 3 poles 3d



Main

| | |
|--|--|
| Device short name | Easypact EZCV250N |
| Circuit breaker application | Distribution |
| Poles description | 3P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [In] rated current | 250 A (40 °C) |
| [Ui] rated insulation voltage | 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-2 |
| [Ue] rated operational voltage | 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker rating code | N |
| Breaking capacity | HIC 50 kA at 240 V AC 50/60 Hz conforming to NE-MA AB1 Icu 85 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 25 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | Ics 10 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 12.5 kA 380...415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 42.5 kA 220...240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| Trip unit technology | Thermal-magnetic |
| Trip unit rating | 150 A (40 °C) |
| Protection type | Earth-leakage protection Overload protection Short-circuit protection |
| Pollution degree | 3 conforming to IEC 60947 |

Complementary

| | |
|----------------------------|---|
| Control type | Toggle |
| Mounting mode | Fixed |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Mechanical durability | 10000 cycles |
| Electrical durability | Category A: 5000 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2 |
| Connection pitch | 35 mm |
| Local signalling | Positive contact indication |
| Neutral protection setting | Without protection |
| Earth-leakage protection | With |
| Height | 165 mm |

| | |
|-------|--------|
| Width | 105 mm |
| Depth | 68 mm |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP20 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -35...85 °C |
| RoHS EUR conformity date | 0801 |
| RoHS EUR status | Compliant |